

Powder	TITEWAD
Target Weight	18.8

Load Parameters	
Bulk Speed	100.00%
Trickle Amplitude	230
Trickle Duration	20
Trickle Start	0.50
Trickle Delay	150
Pulse 1 Start	0.15
Pulse 1 Delay	350
Pulse 2 Start	0.08
Pulse 2 Delay	400
Accuracy ±	0.02

Success %	100.00%
Average Dispense Time (seconds)	10.05



Count	Dispensed (GN)	Time (seconds)
1	18.8	8
2	18.8	10
3	18.8	7
4	18.82	8
5	18.8	8
6	18.8	11
7	18.8	11
8	18.82	11
9	18.8	11
10	18.82	6
11	18.8	8
12	18.82	9
13	18.8	6
14	18.78	10
15	18.78	10
16	18.8	11
17	18.8	9
18	18.78	11
19	18.8	13
20	18.8	13
21	18.8	11
22	18.8	12
23	18.8	8
24	18.78	13
25	18.8	10
26	18.82	11
27	18.82	11
28	18.8	9
29	18.8	15
30	18.8	7
31	18.8	11
32	18.8	10
33	18.8	13
34	18.8	6
35	18.82	9
36	18.8	11
37	18.8	13
38	18.82	11
39	18.8	11
40	18.8	9